

01-0001 Motoren- und Typenübersicht

Motor	Typ	Verkaufs- bezeichnung	Leistung in kW bei 1/min	Verdichtung $\varepsilon : 1$
116.960 116.960 NV 116.960 (J) (USA)	107.025	380 SLC	160/5500 145/5500 120/4750	9,0 7,5 8,3
116.960 116.960 NV 116.960 (AUS) 116.960 (J) (USA)	107.045	380 SL	160/5500 145/5500 145/5500 120/4750	9,0 7,5 8,3 8,3
116.961 116.961 NV	126.032	380 SE	160/5500 145/5500	9,0 7,5
116.961 116.961 NV 116.961 (AUS) (S) 116.961 (J) (USA)	126.033	380 SEL	160/5500 145/5500 145/5500 120/4750	9,0 7,5 8,3 8,3
116.962 116.962 NV 116.962 (AUS) (CH) (S) 116.962 (J) (USA)	107.045	380 SL	150/5250 135/5500 145/5500 120/4750	9,4 7,5 8,3 8,3
116.963 116.963 KAT, (USA) 116.963 NV 116.963 (AUS) (CH) (S)	126.032	380 SE	150/5250 120/4750 135/5500 145/5500	9,4 8,3 7,5 8,3
116.963 116.963 NV 116.963 (AUS) (CH) (S) 116.963 KAT, (J) (USA)	126.033	380 SEL	150/5250 135/5500 145/5500 120/4750	9,4 7,5 8,3 8,3
116.963 116.963 NV 116.963 (AUS) (CH) (S) 116.963 KAT, (J) (USA)	126.043	380 SEC	150/5250 135/5500 145/5500 120/4750	9,4 7,5 8,3 8,3
116.964 RÜF, (CH) (S) 116.964 KAT, (CH) 116.954 NV	107.047	420 SL	160/5200 150/5200 150/5200	9,0 9,0 8,0
116.965 RÜF, (CH) 116.965 KAT, (CH) 116.965 NV 116.965 RÜF 116.965 KAT	126.034	420 SE	160/5200 150/5200 150/5200 170/5400 165/5400	9,0 9,0 8,0 10,0 10,0

Motor	Typ	Verkaufs- bezeichnung	Leistung in kW bei 1/min	Verdichtung $\varepsilon : 1$
116.965 RÜF, (CH) (S)	126.035	420 SEL	160/5200	9,0
116.965 KAT, (AUS) (CH) (J) (USA)			150/5200	9,0
116.965 NV			150/5200	8,0
116.965 RÜF			170/5400	10,0
116.965 KAT			165/5400	10,0
116.965 RÜF, (CH) (S)	126.046	420 SEC	160/5200	9,0
116.965 KAT, (CH)			150/5200	9,0
116.965 NV			150/5200	8,0
116.965 RÜF			170/5400	10,0
116.965 KAT			165/5400	10,0
117.960	107.026	500 SLC	177/4750	8,8
117.960 NV			165/4750	7,5
117.960	107.046	500 SL	177/4750	8,8
117.960 NV			165/4750	7,5
117.961	126.036	500 SE	177/4 50	8,8
117.961			165/4750	7,5
117.961	126.037	500 SEL	177/4750	8,8
117.961 NV			165/4750	7,5
117.962	107.046	500 SL	170/4750	9,2
117.962 NV			160/4750	7,5
117.963	126.036	500 SE	170/4750	9,2
117.963 NV			160/4750	7,5
117.963	126.037	500 SEL	170/4750	9,2
117.963 NV			160/4750	7,5
117.963 (CH) (S)			170/4750	9,2
117.963 (J) (USA)			137/4500	8,0
117.963				
117.963	126.044	500 SEC	170/4750	9,2
117.963 NV			160/4750	7,5
117.963 (CH) (S)			170/4750	9,2
117.963 (J) (USA)			137/4500	8,0
117.963				
117.964 RÜF	107.046	500 SL	180/4750	9,0
117.964 KAT			164/4700	9,0
117.964 NV			170/4750	8,0
117.965 RÜF	126.036	500 SE	180/4750	9,0
117.965 KAT, (CH)			164/4700	9,0
117.965 NV			170/4750	8,0
117.965 RÜF			195/5200	10,0
117.965 KAT			185/5200	10,0
117.965 RÜF	126.037	500 SEL	180/4750	9,0
117.965 KAT, (CH)			164/4700	9,0
117.965 NV			170/4750	8,0
117.965 RÜF			195/5200	10,0
117.965 KAT			185/5200	10,0

Motor	Typ	Verkaufs- bezeichnung	Leistung in kW bei 1/min	Verdichtung $\varepsilon : 1$
117.965 RÜF	126.044	500 SEC	180/4750	9,0
117.965 KAT, (CH)			164/4700	9,0
117.965 NV			170/4750	8,0
117.965 RÜF			195/5200	10,0
117.965 KAT			185/5200	10,0
117.967 (AUS)	107.048	560 SL	175/4750	9,0
117.967 (J) (USA)			173/4750	9,0
117.968 RÜF	126.038	560 SE	220/5000	10,0
117.968 KAT			205/5200	10,0
117.968 NV			200/5000	8,0
117.968 RÜF	126.039	560 SEL	200/5000	9,0
117.968 KAT, (AUS) (CH)			178/4800	9,0
117.968 (J) (USA)			180/4800	9,0
117.968			220/5000	10,0
117.968 RÜF			220/5000	10,0
117.968 KAT			205/5200	10,0
117.968 NV			200/5000	8,0
117.968 RÜF	126.045	560 SEC	200/5000	9,0
117.968 KAT, (AUS) (CH)			178/4800	9,0
117.986			220/5000	10,0
117.968 (J) (USA)			180/4800	9,0
117.968 RÜF			220/5000	10,0
117.968 KAT			205/5200	10,0
117.968 NV			200/5000	8,0

NV = Niederverdichtet, SA = Sonderausführung, KAT = Katalysator
RÜF = Rückrüstfahrzeug